

 ISO 9001 CERTIFIED	RISLONE TECHNICAL BULLETIN	
	Tech Bulletin #: TB-41211-1	Page 1 of 1
	Date 1 st Issued: 27 February 2013	Date Revised: 23 July, 2013
	Rislone Radiator 10 Minute Flush	Part #: 41211

RADIATOR 10 MINUTE FLUSH

Rislone Radiator 10-Minute Flush is fast, easy and safe to use. Contains no acid, needs no neutralizing. Compatible with all automotive cooling systems. Safe to use on Aluminum and Plastic Radiators. The best product to use when performing a normal cooling system service, like an antifreeze flush and fill.

- Use every time changing antifreeze.

DANGER: Opening cooling system while engine is hot or running may cause severe burns.

DISPOSAL: Observe local laws and regulations. Where permitted, dispose of in sanitary sewer systems. Never pour onto the ground or storm sewer system.

NOTE: Protect from freezing.

INSTRUCTIONS

1. Allow engine to cool. Drain system. Close drain.
2. Add entire contents of bottle and refill system with water. Reinstall cap.
3. After engine reaches normal operating temperature, run engine for 10 minutes with heater on and air conditioner off.
4. Allow engine to cool. Flush cooling system and reservoir until water runs clear.
5. Close drain. Refill cooling system and reservoir with manufacturer's recommended antifreeze / water mixture.

DOSAGE

1 bottle cleans a standard passenger car / Utes / light truck. For larger systems use one bottle for every 12 litres of capacity.



Part Number:	41211
UPC Item:	0 78615 41211 2
UPC Case:	1 00 78615 41211 9
Bottle Size:	355 mL
Bottle Size (cm):	6.4 x 6.4 x 15.5
Bottle Cube:	635
Case Pack:	6 bottles
Case Size (cm):	19.8 x 13.4 x 16.5
Case Cube:	4410
Case Weight (kg):	2.5
Pallet:	TI 44 HI 7 Total 308
Pallet Height (m):	1.3